

GU10 ECO DIM

Direct replacement of Halogen GU10

- Energy savings up to 90% comparing with incandescent
- Lifetime up to 20000hrs, covered by 2 years warranty
- CRI up to Ra90
- No UV & IR rays, enviromental friendly
- Excellent dimming performance with various dimmers
- Max height only 54mm, suitable for most fixtures

Light Color



CRI: Ra 90

Housing Material

Heatsink – Built-in Alu heatsink
Lens - PC

Finishing - crystal plastic


IP Rating

IP42

Dimmability

Compatible with most
leading edge or trailing edge dimmers

Dimension Drawings



CP	Watt*	Volt	Flux*	CCT	Angle	CRI*	SDCM	Dimmable
EP16E-5.2W0P27	5,2W	220-240Vac	410lm	2700K	38/60D	Ra90	4 Steps	Yes
EP16E-5.2W0P30	5,2W	220-240Vac	430lm	3000K	38/60D	Ra90	4 Steps	Yes
EP16E-5.2W0P40	5,2W	220-240Vac	450lm	4000K	38/60D	Ra90	4 Steps	Yes
EP16E-5.2W0PTW	5,2W	220-240Vac	400lm	2200-3000K	38/60D	Ra90	4 Steps	Yes

*Amoluce maintains a tolerance of $\pm 10\%$ on flux and power measurements, and ± 2 on CRI

** Testing voltage is 230Vac 50/60Hz , ambient temperature 25 Celsius Degrees